

INTERNATIONAL VERSION



Back of the packaging with international version

Type	CR 1216*	CR 1220*	CR 1225*	CR 1616*	CR 1620*	CR 1632*	CR 2320*	CR 1/3 N*	V 28 PXL*	V 8 GS/391
IEC	CR 1216	CR 1220	CR 1225	CR 1616	CR 1620	CR 1632	CR 2320	-	2 CR 11108	SR 55
Order-No./ consumer unit	06216 101 401	06220 101 401	06225 101 401	06616 101 401	06620 101 401	06632 101 401	06320 101 401	06131 101 401	06231 101 401	04173 101 401
Order-No./ consumer unit International version	-	06220 112 401	-	06616 112 401	06620 112 401	06632 112 401	--	-	-	-
Batteries/ consumer unit	1	1	1	1	1	1	1	1	1	1
Width (mm) Blister	56	56	56	56	56	56	56	56	56	56
Height (mm) Blister	65	65	65	65	65	65	65	65	65	65
Depth (mm) Blister	7.5	7.5	7.5	7.5	7.5	7.5	7.5	13.5	17	7.5
Weight (g) Bister	3	3	3	4	4	4	5	6	11	3
Minimum pieces/ shipment unit	10	10	10	10	10	10	10	10	10	10
Innecarton	10	10	10	10	10	10	10	10	10	10
Mastercarton	100	100	100	100	100	100	100	100	100	100
Voltage (V)	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	6.0	1.55
Electrochemical System	Lithium	Lithium	Lithium	Lithium	Lithium	Lithium	Lithium	Lithium	Lithium	Silver oxide
Typical capacity (mAh)	25	35	48	55	70	135	135	170	170	40
Height (mm) Battery	1.6	2.0	2.5	1.6	2.0	3.2	2.0	10.8	25.1	2.1
Diameter (mm) Battery	12.5	12.5	12.5	16.0	16.0	16.0	23.0	11.6	13.0	11.6
Weight (g) Battery	0.7	0.8	0.9	1.2	1.2	1.8	2.9	3.0	8.8	0.9
Details	Page 46	Page 46	Page 46	Page 46	Page 46	Page 46	Page 46	Page 46	Page 46	Page 46
EAN/GTIN/ consumer unit										

GENERAL PURPOSE

RECHARGEABLE

PORTABLE POWER

PROFESSIONAL/BUTTON CELLS

FLASHLIGHTS AND BULBS

PRODUCT DISPLAY SYSTEMS

ASSORTMENT OVERVIEW