Product data sheet Characteristics

XVBC9M

Ø 70 mm audible unit - adjustable buzzer - 70...90 dB - 120..230 V

noise level: 70...90 dB at 1 m



Main	
Range of product	Harmony XVB Universal
Product or component type	Indicator bank
Beacon or indicator bank unit type	Audible unit
Mounting diameter	70 mm
Component name	XVBC
Noise level	7090 dB at 1 m
[Us] rated supply voltage	120230 V AC

Complementary

Signalling type	Continuous or intermittent buzzer	_
Assembly style	Customer assembly, up to 5 units	
Connections - terminals	Screw clamp terminals : <= 1 x 1.5 mm² with cable end	
[Ui] rated insulation voltage	250 V conforming to IEC 60947-1	
Nominal voltage limit	0.851.1 Un conforming to IEC 60947-5-1	
Current consumption	< 25 mA	
[Uimp] rated impulse withstand voltage	4 kV conforming to IEC 60947-1	
Fundamental frequency	2.8 kHz	
Product weight	0.18 kg	

Environment

Product certifications	CCC	
	CSA C22-2 No 14	
	GOST	
	UL 508	
Standards	EN/IEC 60947-5-1	
Protective treatment	TC	
Ambient air temperature for storage	-4070 °C	
Ambient air temperature for operation	-2550 °C	
Class of protection against electric shock	Class I on support tube conforming to IEC 61140	
	Class II on base unit conforming to IEC 61140	
IP degree of protection	IP65 on fixing base XVBZ0. conforming to IEC 60529	
	IP66 on base unit conforming to IEC 60529	
NEMA degree of protection	NEMA 4X (indoor) conforming to UL 508	
RoHS EUR conformity date	0601	
RoHS EUR status	Compliant	