Product data sheet Characteristics

XVBC2M4

Ø 70 mm illuminated unit - steady - red - IP65 -230 V

power dissipation in W:



Main	
Range of product	Harmony XVB Universal
Product or component type	Indicator bank
Beacon or indicator bank unit type	Illuminated unit
Signalling type	Steady
Mounting diameter	70 mm
Component name	XVBC
Material	Polycarbonate
Light source	Red integral LED
Bulb type	Protected LED
[Us] rated supply volt-	230 V AC

Complementary

Assembly style	Customer assembly, up to 5 units	
Connections - terminals	Screw clamp terminals : <= 1 x 1.5 mm² with cable end	
[Ui] rated insulation voltage	250 V conforming to IEC 60947-1	
Nominal voltage limit	0.851.1 Un conforming to IEC 60947-5-1	
Current consumption	< 17 mA AC	
[Uimp] rated impulse withstand voltage	4 kV conforming to IEC 60947-1	
Product weight	0.15 kg	

age

Environment

Pollution degree	2	
Product certifications	CCC CSA C22-2 No 14 GOST UL 508	
Standards	EN/IEC 60947-5-1	
Protective treatment	TC	
Ambient air temperature for storage	-4070 °C	
Ambient air temperature for operation	-2550 °C	
Class of protection against electric shock	Class I on support tube conforming to IEC 61140 Class II on base unit conforming to IEC 61140	
IP degree of protection	IP65 on fixing base XVBZ0. conforming to IEC 60529 IP66 on base unit conforming to IEC 60529	
NEMA degree of protection	NEMA 4X indoor conforming to UL 508	
RoHS EUR conformity date	0730	
RoHS EUR status	Compliant	