

Automatische beveiliging *Sécurité automatique*

Beveiliging PRI / *protection PRI*Beveiliging SEC / *protection* SEC

 ingebouwde thermische
zekering (uitgezonderd 100 W)
*système de sécurité incorporé
(excepte 100 W)*

 ingebouwd beveiligingssysteem
 herstellend na :

- kortsluiting
- overbelasting
- oververhitting

EN 60 742 EN 61 558 VDE 0551

IP 20
ta 40°C

100 W : zelfherstellend;
150 W - 400 W : manueel herstelbaar

*système de sécurité incorporé
réparable après : - court-circuit
- surcharge
- surchauffe*

100 W : auto-réparable
150 W - 400 W : réparable manuellement

E 212 SC 100 SKA





E 12 SC 150 SKA
E 12 SC 250 SKA



E 12 SC 300 SKA
E 212 SC 400 SKA



Type Type	Code Code	Gewicht Poids	P (Lampen) P (Lampes)	U pri U pri	U sec U sec	Pri Pri	Sec Sec
E 212 SC 100 SKA	1480	1,8 kg	100 W	230 V-240 V	11,6 V	4 mm ² schroefklem borne à vis	4 mm ² (2 x) schroef- klemmen bornes à vis
UTE C15-559							
   						bevestigingsvoetjes bijgeleverd livré avec pattes de fixation	
montage op DIN-rail met hulpstuk U 4174 / montage sur DIN-rail avec auxiliaire U 4174							
Type Type	Code Code	Gewicht Poids	P (Lampen) P (Lampes)	U pri U pri	U sec U sec	Pri Pri	Sec Sec
E 12 SC 150 SKA	1533	2,7 kg	150 W	230 V-240 V	11,6 V	4 mm ²	4 mm ²
E 12 SC 250 SKA	1534	3,7 kg	250 W	230 V-240 V	11,6 V	4 mm ² schroefklem borne à vis	4 mm ² schroefklem borne à vis
UTE C15-559							
 						bevestigingsvoetjes bijgeleverd livré avec pattes de fixation	
Type Type	Code Code	Gewicht Poids	P (Lampen) P (Lampes)	U pri U pri	U sec U sec	Pri Pri	Sec Sec
E 12 SC 300 SKA	1535	6,3 kg	300 W	230 V-240 V	11,6 V	6 mm ²	6 mm ²
E 212 SC 400 SKA	1449	6,4 kg	400 W	230 V-240 V	11,6 V	6 mm ² schroefklem borne à vis	6 mm ² (2 x) schroef- klemmen bornes à vis
UTE C15-559							
 