

Connection Box Flush Mount, 3 Gangs, 213 x 71 x 50 mm



Basic data:

| | |
|------|---------------|
| ID | 0026000019 |
| GTIN | 7630268409876 |



Features:

- Halogen-free Polyvinyl Chloride or Polypropylene
- Wide flange to avoid sinking
- Metal clamp
- Partition wall type fasteners
- Vertical or horizontal installation
- NF 60670 standard
- Resistant to incandescent electric wire (850°C)
- Mechanical resistance: IP40, IK04
- Optimized storage and use between -5°C and +50°C
- BBC: EN 13141 standard, airflow test

Technical data:

| | |
|-------------------------------|------------------------|
| Max. conductor cross section: | 6 mm ² |
| Equipped with: | None |
| Shape: | Oval |
| Mounting method: | Wall-/ceiling mounting |
| For tube diameter: | Other |
| Inlet from the rear: | Yes |
| Length: | 213 mm |
| Width: | 71 mm |
| Depth: | 50 mm |
| Number of inlets: | 24 |
| Type of housing feed-through: | Seal membrane |
| Material: | Plastic |
| Halogen free: | Yes |
| Surface protection: | Untreated |
| Colour: | Grey |
| Degree of protection (IP): | IP40 |
| Cover model: | None |
| Circuit integrity: | None |
| Operating temperature: | 60 °C |
| For Ex-zone gas: | None |
| For Ex-Zone dust: | None |