

SensIQ S EVO incl. corner bracket
and remote control RC9

SensIQ S EVO

New: bidirectional Smart Remote communication

- Detection Area 3 x 100° zones adjustable from 2- 20m
- 4 pyro detectors for best detection in class
- **NEW**: with remote control RC9 and full Smart Remote support
- **NEW**: Brightness dependent switch off although occupancy
→ presence detector logic
- Send and read values of the sensor
- 1360 switching zones for perfect detection outdoors



SensIQ S EVO

New: bidirectional Smart Remote communication

Technical Data

Dimensions (H x W x D): 74 x 114 x 128 mm
 Voltage: 100 – 240 V, 50/ 60 Hz
 Output: max. 2000/1200 W , 230/120 V
 max. 8 pcs. LED-bulbs / energy savings bulbs C<176µF (capacitive)
 Mounting height: 2 – 5 m
 Angle of detection: 300° with 180° angle of aperture, sneak-by guard
 Reach: adjustable in 3 direction, max. 2 - 20 m
 Time setting : 5 sec. – 15 min, Pulse-Mode (approx. 2 sec.)
 Brightness setting : 2 - 2000 Lux
 Manual override: 4 h
 Temperature range: -20° C to +50° C
 IP/ protection class : IP 54 / II
 Scope of delivery: Incl. Corner bracket and remote control RC9

Customs tariff number: 85365080
 Country of origin: Romania
 Region of origin: 03



EAN-Code	Art.-No.	Bezeichnung Description	VE min.order quan.
4007841 034955	034955	SensIQ S White EVO	1
4007841 034962	034962	SensIQ S Inox EVO	1
4007841 034979	034979	SensIQ S black EVO	1