



Main

Range of product	Harmony XVB Universal
Product or component type	Base unit
Mounting diameter	70 mm
Component name	XVBC
Indicator bank base type	Standard
Product destination	Banks without flash discharge tube unit
Material	Glass reinforced polyamide (base unit)
Cable entry	Bottom or side entry

Complementary

Fixing mode	Direct or tube fixing
Assembly style	Customer assembly, up to 5 units
Product weight	0.16 kg

Environment

Product certifications	CCC CSA C22-2 No 14 GOST UL 508
Standards	EN/IEC 60947-5-1
Protective treatment	TC
Ambient air temperature for storage	-40...70 °C
NEMA degree of protection	NEMA 4X (indoor) conforming to UL 508
RoHS EUR conformity date	0808
RoHS EUR status	Compliant

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.